

RACKOM- 24U Floor Standing Server Rack

Brand- RACKOm

- Usability- Network Switches/Routers/ DVR/ Audio- Visual Equipment/Broadcasting Equipment /Servers
- Front Door- Glass Door Or Full perforated With Lock
- Rear door- Half Perforated and Full Perforation Steel Door With Lock
- Side Panels- Removable With Slam Latch and Lockable Provision
- Cable Entry Cut- Top/ Bottom
- 4 Pair Heavy Duty (2.0mm) Depth Support Channel Fitted On Front & Rear Pillar
- 2 Pair Heavy Duty (2.0mm) Vertical Mounting Rail Channel Fitted On Front & Rear Pillar
- Cooling Option- 4 fan Provision mounted on Top Panel
- Load Bearing Capacity up to 600 to 1000 KG
- Construction- Dismantle Construction Overall 1.2mm Thick (18 gauge), Load Bearing angles are 2 MM
- Power Distribution Unit- Horizontal Vertical Optional
- Cable Management- Horizontal & vertical
- Sliding Tray For Equipment and Keyboard - Optional
- Color- light Grey Powder Coated (RAL 7035) and RAL 9005 Black (as per Requirement)

Product Part No.	Height in U	Overall Height with Castor/Leg	Usable Height	Overall Width	Usable Width	Overall Depth	Usable Depth
RSFS0024-001 (24U 600x600)	24U	1255mm (49.40 Inch)	1066.8mm (42.00 Inch)	600mm	482.6mm 19 Inch	600mm	480mm (18.89 inch)
RSFS0024-002 (24U 600x800)	24U	1255mm (49.40 Inch)	1066.8mm (42.00 Inch)	600mm	482.6mm 19 Inch	800mm	680mm (26.77 inch)
RSFS0024-003 (24U 600x1000)	24U	1255mm (49.40 Inch)	1066.8mm (42.00 Inch)	600mm	482.6mm 19 Inch	1000mm	880mm (34.64 inch)
RSFS0024-004 (24U 800x800)	24U	1255mm (49.40 Inch)	1066.8mm (42.00 Inch)	800mm	482.6mm 19 Inch	800mm	680mm (26.77 inch)
RSFS0024-005 (24U 800x1000)	24U	1255mm (49.40 Inch)	1066.8mm (42.00 Inch)	800mm	482.6mm 19 Inch	1000mm	880mm (34.64 inch)
RSFS0024-006 (24U 600x1200)	24U	1255mm (49.40 Inch)	1066.8mm (42.00 Inch)	600mm	482.6mm 19 Inch	1200mm	1080mm (42.51 inch)
RSFS0024-007 (24U 800x1200)	24U	1255mm (49.40 Inch)	1066.8mm (42.00 Inch)	800mm	482.6mm 19 Inch	1200mm	1080mm (42.51 inch)